

850 Purchase Order

X12/V4060/850: 850 Purchase Order

Status: Final

Modified: 03/03/2005

850 Purchase Order

Functional Group=PO

This X12 Transaction Set contains the format and establishes the data contents of the Purchase Order Transaction Set (850) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business and industry practice relative to the placement of purchase orders for goods and services. This transaction set should not be used to convey purchase order changes or purchase order acknowledgment information.

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
0100	ST	Transaction Set Header	M	1			Must use
0200	BEG	Beginning Segment for Purchase Order	M	1			Must use
0400	CUR	Currency	O	1			Used
0500	REF	Reference Information	O	>1			Used

<u>LOOP ID - SAC</u>					<u>25</u>		
1200	SAC	Service, Promotion, Allowance, or Charge Information	O	1			Used
1500	DTM	Date/Time Reference	O	10			Must use
2400	TD5	Carrier Details (Routing Sequence/Transit Time)	O	>1			Used

<u>LOOP ID - N1</u>					<u>200</u>		
3100	N1	Party Identification	O	1			Must use
3300	N3	Party Location	O	2			Used
3400	N4	Geographic Location	O	>1			Used
3500	REF	Reference Information	O	12			Used
3600	PER	Administrative Communications Contact	O	>1			Used

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
<u>LOOP ID - PO1</u>					<u>100000</u>	<u>N2/0100L</u>	
0100	PO1	Baseline Item Data	M	1		N2/0100	Must use
<u>LOOP ID - PID</u>					<u>1000</u>		
0500	PID	Product/Item Description	O	1			Used
0900	PO4	Item Physical Details	O	>1			Used

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
<u>LOOP ID - CTT</u>					<u>1</u>	<u>N3/0100L</u>	

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
0100	CTT	Transaction Totals	O	1		N3/0100	Used
0200	AMT	Monetary Amount Information	O	1		N3/0200	Used
0300	SE	Transaction Set Trailer	M	1			Must use

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

Notes:

- 2/0100L PO102 is required.
- 2/0100 PO102 is required.
- 3/0100L The number of line items (CTT01) is the accumulation of the number of PO1 segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.
- 3/0100 The number of line items (CTT01) is the accumulation of the number of PO1 segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.
- 3/0200 If AMT is used in the summary area, then AMT01 will = TT and AMT02 will indicate total transaction amount as calculated by the sender.

ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

User Option (Usage): Must use

To start and identify an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier	M	ID	2/2	Must use
Description: Code identifying the type of information in the Authorization Information						
Code Name						
00 No Authorization Information Present (No Meaningful Information in I02)						
ISA02	I02	Authorization Information	M	AN	10/10	Must use
Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)						
ISA03	I03	Security Information Qualifier	M	ID	2/2	Must use
Description: Code identifying the type of information in the Security Information						
Code Name						
00 No Security Information Present (No Meaningful Information in I04)						
ISA04	I04	Security Information	M	AN	10/10	Must use
Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)						
ISA05	I05	Interchange ID Qualifier	M	ID	2/2	Must use
Description: Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified						
Code Name						
14 Duns Plus Suffix						
ISA06	I06	Interchange Sender ID	M	AN	15/15	Must use
Description: Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element						
Code Name						
0722717110 US Production 100						
0722717111 Canada Production CAP						
ISA07	I05	Interchange ID Qualifier	M	ID	2/2	Must use
Description: Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified						
All valid standard codes are used.						

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA08	I07	Interchange Receiver ID	M	AN	15/15	Must use
		Description: Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them				
ISA09	I08	Interchange Date	M	DT	6/6	Must use
		Description: Date of the interchange				
ISA10	I09	Interchange Time	M	TM	4/4	Must use
		Description: Time of the interchange				
ISA11	I65	Repetition Separator	M		1/1	Must use
		Description: Type is not applicable; the repetition separator is a delimiter and not a data element; this field provides the delimiter used to separate repeated occurrences of a simple data element or a composite data structure; this value must be different than the data element separator, component element separator, and the segment terminator				
		Code Name				
		:	Colon			
		@	At			
]	Bracket			
		^	Carrot			
			Pipe			
		The Home Depot Requirements:				
		<i>This separator can be any non-alpha-numeric character that is also not used as an element separator, segment terminator or elsewhere in the data. If you need your Repetition Separator added to the list to complete testing, please call Home Depot's Electronic Partnership Development Team at 770-433-8211 x10036, option 2.</i>				
ISA12	I11	Interchange Control Version Number	M	ID	5/5	Must use
		Description: Code specifying the version number of the interchange control segments				
		Code Name				
		00406	Standards Approved for Publication by ASC X12 Procedures Review Board through October 2002			
ISA13	I12	Interchange Control Number	M	N0	9/9	Must use
		Description: A control number assigned by the interchange sender				
ISA14	I13	Acknowledgment Requested	M	ID	1/1	Must use
		Description: Code indicating sender's request for an interchange acknowledgment				
		Code Name				
		0	No Interchange Acknowledgment Requested			
ISA15	I14	Interchange Usage Indicator	M	ID	1/1	Must use
		Description: Code indicating whether data enclosed by this interchange envelope is test, production or information				
		All valid standard codes are used.				
ISA16	I15	Component Element Separator	M		1/1	Must use
		Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements				

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		within a composite data structure; this value must be different than the data element separator and the segment terminator				

GS Functional Group Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Must use

To indicate the beginning of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code	M	ID	2/2	Must use
		Description: Code identifying a group of application related transaction sets				
		<u>Code</u>	<u>Name</u>			
		PO	Purchase Order (850)			
GS02	142	Application Sender's Code	M	AN	2/15	Must use
		Description: Code identifying party sending transmission; codes agreed to by trading partners				
		<u>Code</u>	<u>Name</u>			
		072271711	US Production			
		072271711	Canada Production			
		C				
GS03	124	Application Receiver's Code	M	AN	2/15	Must use
		Description: Code identifying party receiving transmission; codes agreed to by trading partners				
GS04	373	Date	M	DT	8/8	Must use
		Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year				
GS05	337	Time	M	TM	4/8	Must use
		Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)				
GS06	28	Group Control Number	M	N0	1/9	Must use
		Description: Assigned number originated and maintained by the sender				
GS07	455	Responsible Agency Code	M	ID	1/2	Must use
		Description: Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480				
		<u>Code</u>	<u>Name</u>			
		X	Accredited Standards Committee X12			
GS08	480	Version / Release / Industry Identifier Code	M	AN	1/12	Must use
		Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the				

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed				
		<u>Code</u>				
		<u>Name</u>				
		004060				Standards Approved for Publication by ASC X12 Procedures Review Board through October 2002

Semantics:

1. GS04 is the group date.
2. GS05 is the group time.
3. The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

Comments:

1. A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.

ST Transaction Set Header

Pos: 0100	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use
Description: Code uniquely identifying a Transaction Set						
Code Name						
850 Purchase Order						
ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

Semantics:

1. The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
2. The implementation convention reference (ST03) is used by the translation routines of the interchange partners to select the appropriate implementation convention to match the transaction set definition. When used, this implementation convention reference takes precedence over the implementation reference specified in the GS08.

BEG Beginning Segment for Purchase Order

Pos: 0200	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 5

User Option (Usage): Must use

To indicate the beginning of the Purchase Order Transaction Set and transmit identifying numbers and dates

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BEG01	353	Transaction Set Purpose Code	M	ID	2/2	Must use
Description: Code identifying purpose of transaction set						
Code Name						
00 Original						
01 Cancellation						
22 Information Copy						
BEG02	92	Purchase Order Type Code	M	ID	2/2	Must use
Description: Code specifying the type of Purchase Order						
Code Name						
CN Consigned Order						
DR Direct Ship						
Description: Vendor ships directly to customer						
The Home Depot Requirements:						
<i>Qualifier used for homedepot.com Purchase Orders only.</i>						
NE New Order						
NS New Store Opening						
OS Special Order						
BEG03	324	Purchase Order Number	M	AN	1/22	Must use
Description: Identifying number for Purchase Order assigned by the orderer/purchaser						
The Home Depot Requirements: <i>The Home Depot 8 digit Purchase Order Number</i>						
BEG05	373	Date	M	DT	8/8	Must use
Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year						
BEG06	367	Contract Number	O	AN	1/30	Used
Description: Contract number						

Semantics:

1. BEG05 is the date assigned by the purchaser to purchase order.

CUR Currency

Pos: 0400	Max: 1
Heading - Optional	
Loop: N/A	Elements: 3

User Option (Usage): Used

To specify the currency (dollars, pounds, francs, etc.) used in a transaction

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CUR01	98	Entity Identifier Code	M	ID	2/3	Must use
Description: Code identifying an organizational entity, a physical location, property or an individual						
Code Name						
BY Buying Party (Purchaser)						
CUR02	100	Currency Code	M	ID	3/3	Must use
Description: Code (Standard ISO) for country in whose currency the charges are specified						
CUR03	280	Exchange Rate	O	R	4/10	Used
Description: Value to be used as a multiplier conversion factor to convert monetary value from one currency to another						
The Home Depot Requirements: <i>This element is only sent to Canadian suppliers that are paid in US Dollars.</i>						

Syntax Rules:

1. C0807 - If CUR08 is present, then CUR07 is required.
2. C0907 - If CUR09 is present, then CUR07 is required.
3. L101112 - If CUR10 is present, then at least one of CUR11 or CUR12 is required.
4. C1110 - If CUR11 is present, then CUR10 is required.
5. C1210 - If CUR12 is present, then CUR10 is required.
6. L131415 - If CUR13 is present, then at least one of CUR14 or CUR15 is required.
7. C1413 - If CUR14 is present, then CUR13 is required.
8. C1513 - If CUR15 is present, then CUR13 is required.
9. L161718 - If CUR16 is present, then at least one of CUR17 or CUR18 is required.
10. C1716 - If CUR17 is present, then CUR16 is required.
11. C1816 - If CUR18 is present, then CUR16 is required.
12. L192021 - If CUR19 is present, then at least one of CUR20 or CUR21 is required.
13. C2019 - If CUR20 is present, then CUR19 is required.
14. C2119 - If CUR21 is present, then CUR19 is required.

Comments:

1. See Figures Appendix for examples detailing the use of the CUR segment.

REF Reference Information

Pos: 0500	Max: >1
Heading - Optional	
Loop: N/A	Elements: 3

User Option (Usage): Used

To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

Code Name

CO Customer Order Number

The Home Depot Requirements:

homedepot.com Internet Order Number

S3 Specification Number

The Home Depot Requirements:

Used only for Special Order or homedepot.com Gift Messages.

REF02	127	Reference Identification	X	AN	1/50	Used
-------	-----	--------------------------	---	----	------	------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

The Home Depot Requirements: *Used with CO qualifier for the homedepot.com Internet Order Number*

REF03	352	Description	X	AN	1/80	Used
-------	-----	-------------	---	----	------	------

Description: A free-form description to clarify the related data elements and their content

The Home Depot Requirements: *Used with the S3 qualifier only for Special Orders information or homedepot.com Gift Messages.*

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

Loop SAC

Pos: 1200	Repeat: 25
Optional	
Loop: SAC	Elements: N/A

User Option (Usage): Used

To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
1200	SAC	Service, Promotion, Allowance, or Charge Information	O	1		Used

SAC Service, Promotion, Allowance, or Charge Information

Pos: 1200	Max: 1
Heading - Optional	
Loop: SAC	Elements: 5

User Option (Usage): Used

To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SAC01	248	Allowance or Charge Indicator	M	ID	1/1	Must use

Description: Code which indicates an allowance or charge for the service specified

Code Name

A Allowance
C Charge

SAC02	1300	Service, Promotion, Allowance, or Charge Code	X	ID	4/4	Used
-------	------	--	---	----	-----	------

Description: Code identifying the service, promotion, allowance, or charge

Code Name

E750 New Store Discount
H000 Special Allowance
I170 Trade Discount

SAC06	378	Allowance/Charge Percent Qualifier	X	ID	1/1	Used
-------	-----	---	---	----	-----	------

Description: Code indicating on what basis allowance or charge percent is calculated

Code Name

3 Discount/Gross

SAC07	332	Percent, Decimal Format	X	R	1/6	Used
-------	-----	--------------------------------	---	---	-----	------

Description: Percent given in decimal format (e.g., 0.0 through 100.0 represents 0% through 100%)

SAC12	331	Allowance or Charge Method of Handling Code	O	ID	2/2	Used
-------	-----	--	---	----	-----	------

Description: Code indicating method of handling for an allowance or charge

Code Name

02 Off Invoice

Syntax Rules:

1. R0203 - At least one of SAC02 or SAC03 is required.
2. P0304 - If either SAC03 or SAC04 is present, then the other is required.
3. P0607 - If either SAC06 or SAC07 is present, then the other is required.
4. P0910 - If either SAC09 or SAC10 is present, then the other is required.

5. C1110 - If SAC11 is present, then SAC10 is required.
6. C1413 - If SAC14 is present, then SAC13 is required.
7. C1615 - If SAC16 is present, then SAC15 is required.

Semantics:

1. If SAC01 is "A" or "C", then at least one of SAC05, SAC07, or SAC08 is required.
2. SAC05 is the total amount for the service, promotion, allowance, or charge.
3. If SAC05 is present with SAC07 or SAC08, then SAC05 takes precedence.
4. SAC08 is the allowance or charge rate per unit.
5. SAC10 and SAC11 is the quantity basis when the allowance or charge quantity is different from the purchase order or invoice quantity.
6. SAC10 and SAC11 used together indicate a quantity range, which could be a dollar amount, that is applicable to service, promotion, allowance, or charge.
7. SAC13 is used in conjunction with SAC02 or SAC04 to provide a specific reference number as identified by the code used.
8. SAC14 is used in conjunction with SAC13 to identify an option when there is more than one option of the promotion.
9. SAC16 is used to identify the language being used in SAC15.

Comments:

1. SAC04 may be used to uniquely identify the service, promotion, allowance, or charge. In addition, it may be used in conjunction with SAC03 to further define SAC02.
2. In some business applications, it is necessary to advise the trading partner of the actual dollar amount that a particular allowance, charge, or promotion was based on to reduce ambiguity. This amount is commonly referred to as "Dollar Basis Amount". It is represented in the SAC segment in SAC10 using the qualifier "DO" - Dollars in SAC09.

DTM Date/Time Reference

Pos: 1500	Max: 10
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use

Description: Code specifying type of date or time, or both date and time

Code Name

- 002 Delivery Requested
- 038 Ship No Later
- 061 Cancel if Not Delivered by

DTM02	373	Date	X	DT	8/8	Must use
-------	-----	-------------	---	----	-----	----------

Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

TD5 Carrier Details (Routing Sequence/Transit Time)

Pos: 2400	Max: >1
Heading - Optional	
Loop: N/A	Elements: 1

User Option (Usage): Used

To specify the carrier and sequence of routing and provide transit time information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TD512	284	Service Level Code	X	ID	2/2	Must use

Description: Code indicating the level of transportation service or the billing service offered by the transportation carrier

Code Name

CG Ground

The Home Depot Requirements:

Common Carrier / LTL Carrier

DS Door Service

The Home Depot Requirements:

White Glove Service / Special Delivery

ND Next Day Air

Description: Delivery during business day hours of next business day

The Home Depot Requirements:

Small Package Carrier Only

SC Second Day Air

Description: Delivery during business day hours no later than second business day

The Home Depot Requirements:

Small Package Carrier Only

SG Standard Ground

The Home Depot Requirements:

Small Package Carrier Only

ZZ Mutually Defined

The Home Depot Requirements:

Freight Included

Syntax Rules:

1. R0204050612 - At least one of TD502, TD504, TD505, TD506 or TD512 is required.
2. C0203 - If TD502 is present, then TD503 is required.
3. C0708 - If TD507 is present, then TD508 is required.
4. C1011 - If TD510 is present, then TD511 is required.
5. C1312 - If TD513 is present, then TD512 is required.
6. C1413 - If TD514 is present, then TD513 is required.
7. C1512 - If TD515 is present, then TD512 is required.

Semantics:

1. TD515 is the country where the service is to be performed.

Comments:

1. When specifying a routing sequence to be used for the shipment movement in lieu of specifying each carrier within the movement, use TD502 to identify the party responsible for defining the routing sequence, and use TD503 to identify the actual routing sequence, specified by the party identified in TD502.

The Home Depot Requirements:

The TD5 Segment is mandatory for homedepot.com orders. This segment will be used to communicate how the order is to be shipped.

Loop N1

Pos: 3100	Repeat: 200
Optional	
Loop: N1	Elements: N/A

User Option (Usage): Must use

To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
3100	N1	Party Identification	O	1		Must use
3300	N3	Party Location	O	2		Used
3400	N4	Geographic Location	O	>1		Used
3500	REF	Reference Information	O	12		Used
3600	PER	Administrative Communications Contact	O	>1		Used

N1 Party Identification

Pos: 3100	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Must use

To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use

Description: Code identifying an organizational entity, a physical location, property or an individual

Code Name

BY Buying Party (Purchaser)

The Home Depot Requirements:

Name of the customer that placed the order on homedepot.com.

OB Ordered By

The Home Depot Requirements:

Home Depot ordering store information

ST Ship To

The Home Depot Requirements:

Ship To Address used for Special Orders or homedepot.com Purchase Orders

N102	93	Name	X	AN	1/60	Used
------	----	-------------	---	----	------	------

Description: Free-form name

N103	66	Identification Code Qualifier	X	ID	1/2	Used
------	----	--------------------------------------	---	----	-----	------

Description: Code designating the system/method of code structure used for Identification Code (67)

The Home Depot Requirements: *Only used with the OB qualifier.*

Code Name

92 Assigned by Buyer or Buyer's Agent

N104	67	Identification Code	X	AN	2/80	Used
------	----	----------------------------	---	----	------	------

Description: Code identifying a party or other code

The Home Depot Requirements: *Ordering Store Number - Only used with the OB qualifier.*

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

N3 Party Location

Pos: 3300	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information	M	AN	1/55	Must use
		Description: Address information				
N302	166	Address Information	O	AN	1/55	Used
		Description: Address information				

N4 Geographic Location

Pos: 3400	Max: >1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	O	AN	2/30	Used
		Description: Free-form text for city name				
N402	156	State or Province Code	X	ID	2/2	Used
		Description: Code (Standard State/Province) as defined by appropriate government agency				
N403	116	Postal Code	O	ID	3/15	Used
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				
N404	26	Country Code	X	ID	2/3	Used
		Description: Code identifying the country				

Syntax Rules:

1. E0207 - Only one of N402 or N407 may be present.
2. C0605 - If N406 is present, then N405 is required.
3. C0704 - If N407 is present, then N404 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

REF Reference Information

Pos: 3500	Max: 12
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

Code Name

- 3J Office Number
- DP Department Number
- MR Merchandise Type Code
- ST Store Number

REF02	127	Reference Identification	X	AN	1/50	Used
-------	-----	--------------------------	---	----	------	------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

PER Administrative Communications Contact

Pos: 3600	Max: >1
Heading - Optional	
Loop: N1	Elements: 6

User Option (Usage): Used

To identify a person or office to whom administrative communications should be directed

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PER01	366	Contact Function Code	M	ID	2/2	Must use
		Description: Code identifying the major duty or responsibility of the person or group named				
		Code Name				
		NT				Notification Contact
PER02	93	Name	O	AN	1/60	Used
		Description: Free-form name				
PER03	365	Communication Number Qualifier	X	ID	2/2	Used
		Description: Code identifying the type of communication number				
		Code Name				
		TE				Telephone
PER04	364	Communication Number	X	AN	1/256	Used
		Description: Complete communications number including country or area code when applicable				
PER05	365	Communication Number Qualifier	X	ID	2/2	Used
		Description: Code identifying the type of communication number				
		Code Name				
		AP				Alternate Telephone
PER06	364	Communication Number	X	AN	1/256	Used
		Description: Complete communications number including country or area code when applicable				

Syntax Rules:

1. P0304 - If either PER03 or PER04 is present, then the other is required.
2. P0506 - If either PER05 or PER06 is present, then the other is required.
3. P0708 - If either PER07 or PER08 is present, then the other is required.

Loop PO1

Pos: 0100	Repeat: 100000
Mandatory	
Loop: PO1	Elements: N/A

User Option (Usage): Must use

To specify basic and most frequently used line item data

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0100	PO1	Baseline Item Data	M	1		Must use
0500		Loop PID	O		1000	Used
0900	PO4	Item Physical Details	O	>1		Used

PO1 Baseline Item Data

Pos: 0100 Max: 1
 Detail - Mandatory
 Loop: PO1 Elements: 12

User Option (Usage): Must use

To specify basic and most frequently used line item data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO101	350	Assigned Identification	O	AN	1/20	Used
Description: Alphanumeric characters assigned for differentiation within a transaction set						
PO102	380	Quantity	X	R	1/15	Must use
Description: Numeric value of quantity						
PO103	355	Unit or Basis for Measurement Code	O	ID	2/2	Used
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						

Code Name

- BD Bundle
- BF Board Feet
- BG Bag
- BM Bolt
- BX Box
- CA Case
- CT Carton
- EA Each
- FT Foot
- GA Gallon
- LB Pound
- LF Linear Foot
- LN Length
- LY Linear Yard
- MR Meter
- PA Pail
- PC Piece
- PF Pallet (Lift)
- PK Package
- PL Pallet/Unit Load
- PR Pair
- PT Pint
- QT Quart
- RL Roll
- SF Square Foot
- SM Square Meter
- SQ Square

Description: A unit of measure for roofing materials equal to 100 square feet

Code Name

ST Set
 SY Square Yard
 YD Yard

PO104 212 **Unit Price** X R 1/17 Used

Description: Price per unit of product, service, commodity, etc.

PO106 235 **Product/Service ID Qualifier** X ID 2/2 Must use

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

Code Name

IN Buyer's Item Number

The Home Depot Requirements:
homedepot.com Internet Part Number
 Only used for homedepot.com orders.

SK Stock Keeping Unit (SKU)

The Home Depot Requirements:
Home Depot SKU Number

UP UCC - 12

Description: Data structure for the 12 digit EAN.UCC (EAN International.Uniform Code Council) Global Trade Identification Number (GTIN). Also known as the Universal Product Code (U.P.C.)

The Home Depot Requirements:
Product UPC Code

VP Vendor's (Seller's) Part Number

The Home Depot Requirements:
Vendor's Part Number

PO107 234 **Product/Service ID** X AN 1/48 Must use

Description: Identifying number for a product or service

PO108 235 **Product/Service ID Qualifier** X ID 2/2 Used

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

Code Name

IN Buyer's Item Number

The Home Depot Requirements:
homedepot.com Internet Part Number
 Only used for homedepot.com orders.

SK Stock Keeping Unit (SKU)

The Home Depot Requirements:
Home Depot SKU Number

UP UCC - 12

Description: Data structure for the 12 digit EAN.UCC (EAN International.Uniform Code Council) Global Trade Identification Number (GTIN). Also known as the Universal Product Code (U.P.C.)

The Home Depot Requirements:

Code Name

Product UPC Code

VP Vendor's (Seller's) Part Number

The Home Depot Requirements:

Vendor's Part Number

PO109 234 **Product/Service ID** X AN 1/48 Used

Description: Identifying number for a product or service

PO110 235 **Product/Service ID Qualifier** X ID 2/2 Used

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

Code Name

IN Buyer's Item Number

The Home Depot Requirements:

homedepot.com Internet Part Number

Only used for homedepot.com orders.

SK Stock Keeping Unit (SKU)

The Home Depot Requirements:

Home Depot SKU Number

UP UCC - 12

Description: Data structure for the 12 digit EAN.UCC (EAN International.Uniform Code Council) Global Trade Identification Number (GTIN). Also known as the Universal Product Code (U.P.C.)

The Home Depot Requirements:

Product UPC Code

VP Vendor's (Seller's) Part Number

The Home Depot Requirements:

Vendor's Part Number

PO111 234 **Product/Service ID** X AN 1/48 Used

Description: Identifying number for a product or service

PO112 235 **Product/Service ID Qualifier** X ID 2/2 Used

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

Code Name

IN Buyer's Item Number

The Home Depot Requirements:

homedepot.com Internet Part Number

Only used for homedepot.com orders.

SK Stock Keeping Unit (SKU)

The Home Depot Requirements:

Home Depot SKU Number

UP UCC - 12

Description: Data structure for the 12 digit EAN.UCC (EAN International.Uniform Code Council) Global Trade Identification Number (GTIN). Also known as the Universal Product Code (U.P.C.)

<u>Code</u>	<u>Name</u>					
	The Home Depot Requirements:					
	<i>Product UPC Code</i>					
VP	Vendor's (Seller's) Part Number					
	The Home Depot Requirements:					
	<i>Vendor's Part Number</i>					
PO113	234	Product/Service ID	X	AN	1/48	Used
Description: Identifying number for a product or service						

Syntax Rules:

1. C0302 - If PO103 is present, then PO102 is required.
2. C0504 - If PO105 is present, then PO104 is required.
3. P0607 - If either PO106 or PO107 is present, then the other is required.
4. P0809 - If either PO108 or PO109 is present, then the other is required.
5. P1011 - If either PO110 or PO111 is present, then the other is required.
6. P1213 - If either PO112 or PO113 is present, then the other is required.
7. P1415 - If either PO114 or PO115 is present, then the other is required.
8. P1617 - If either PO116 or PO117 is present, then the other is required.
9. P1819 - If either PO118 or PO119 is present, then the other is required.
10. P2021 - If either PO120 or PO121 is present, then the other is required.
11. P2223 - If either PO122 or PO123 is present, then the other is required.
12. P2425 - If either PO124 or PO125 is present, then the other is required.

Semantics:

1. PO102 is quantity ordered.

Comments:

1. See the Data Element Dictionary for a complete list of IDs.
2. PO101 is the line item identification.
3. PO106 through PO125 provide for ten different product/service IDs per each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Loop PID

Pos: 0500	Repeat: 1000
Optional	
Loop: PID	Elements: N/A

User Option (Usage): Used

To describe a product or process in coded or free-form format

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0500	PID	Product/Item Description	O	1		Used

PID Product/Item Description

Pos: 0500	Max: 1
Detail - Optional	
Loop: PID	Elements: 2

User Option (Usage): Used

To describe a product or process in coded or free-form format

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PID01	349	Item Description Type	M	ID	1/1	Must use
		Description: Code indicating the format of a description				
		<u>Code</u> <u>Name</u>				
		F Free-form				
PID05	352	Description	X	AN	1/80	Must use
		Description: A free-form description to clarify the related data elements and their content				

Syntax Rules:

1. C0403 - If PID04 is present, then PID03 is required.
2. R0405 - At least one of PID04 or PID05 is required.
3. C0703 - If PID07 is present, then PID03 is required.
4. C0804 - If PID08 is present, then PID04 is required.
5. C0905 - If PID09 is present, then PID05 is required.

Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.
3. PID07 specifies the individual code list of the agency specified in PID03.

PO4 Item Physical Details

Pos: 0900	Max: >1
Detail - Optional	
Loop: PO1	Elements: 2

User Option (Usage): Used

To specify the physical qualities, packaging, weights, and dimensions relating to the item

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO402	357	Size	X	R	1/8	Used
Description: Size of supplier units in pack						
PO403	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						
All valid standard codes are used.						

Syntax Rules:

1. P0203 - If either PO402 or PO403 is present, then the other is required.
2. C0506 - If PO405 is present, then PO406 is required.
3. P0607 - If either PO406 or PO407 is present, then the other is required.
4. P0809 - If either PO408 or PO409 is present, then the other is required.
5. C1013 - If PO410 is present, then PO413 is required.
6. C1113 - If PO411 is present, then PO413 is required.
7. C1213 - If PO412 is present, then PO413 is required.
8. L13101112 - If PO413 is present, then at least one of PO410, PO411 or PO412 is required.
9. C1716 - If PO417 is present, then PO416 is required.
10. C1804 - If PO418 is present, then PO404 is required.

Semantics:

1. PO415 is used to indicate the relative layer of this package or range of packages within the layers of packaging. Relative Position 1 (value R1) is the innermost package.
2. PO416 is the package identifier or the beginning package identifier in a range of identifiers.
3. PO417 is the ending package identifier in a range of identifiers.
4. PO418 is the number of packages in this layer.

Comments:

1. PO403 - The "Unit or Basis for Measure Code" in this segment position is for purposes of defining the unit of measure of the "Size" identified in the PO402. For example: If the carton contains 24 12-Ounce packages, it would be described as follows: Data element 356 = "24"; Data element 357 = "12"; Data element 355 = "OZ".
2. PO413 defines the unit of measure for PO410, PO411, and PO412.

Loop CTT

Pos: 0100	Repeat: 1
Optional	
Loop: CTT	Elements: N/A

User Option (Usage): Used

To transmit a hash total for a specific element in the transaction set

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0100	CTT	Transaction Totals	O	1		Used
0200	AMT	Monetary Amount Information	O	1		Used

CTT Transaction Totals

Pos: 0100	Max: 1
Summary - Optional	
Loop: CTT	Elements: 2

User Option (Usage): Used

To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use

Description: Total number of line items in the transaction set

CTT02	347	Hash Total	O	R	1/10	Used
-------	-----	-------------------	---	---	------	------

Description: Sum of values of the specified data element. All values in the data element will be summed without regard to decimal points (explicit or implicit) or signs. Truncation will occur on the left most digits if the sum is greater than the maximum size of the hash total of the data element. Example: -.0018 First occurrence of value being hashed. .18 Second occurrence of value being hashed. 1.8 Third occurrence of value being hashed. 18.01 Fourth occurrence of value being hashed. ----- 1855 Hash Total

Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

AMT Monetary Amount Information

Pos: 0200	Max: 1
Summary - Optional	
Loop: CTT	Elements: 2

User Option (Usage): Used

To indicate the total monetary amount

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
AMT01	522	Amount Qualifier Code	M	ID	1/3	Must use
		Description: Code to qualify amount				
		Code Name				
		TT				Total Transaction Amount
AMT02	782	Monetary Amount	M	R	1/18	Must use
		Description: Monetary amount				
		The Home Depot Requirements: Retail total of the order				

SE Transaction Set Trailer

Pos: 0300	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	NO	1/10	Must use
		Description: Total number of segments included in a transaction set including ST and SE segments				
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

Comments:

1. SE is the last segment of each transaction set.

GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To indicate the end of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included	M	N0	1/6	Must use
		Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element				
GE02	28	Group Control Number	M	N0	1/9	Must use
		Description: Assigned number originated and maintained by the sender				

Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups	M	N0	1/5	Must use
		Description: A count of the number of functional groups included in an interchange				
IEA02	I12	Interchange Control Number	M	N0	9/9	Must use
		Description: A control number assigned by the interchange sender				

Table of Contents

850	Purchase Order	2
ISA	Interchange Control Header	4
GS	Functional Group Header	7
ST	Transaction Set Header	9
BEG	Beginning Segment for Purchase Order	10
CUR	Currency	11
REF	Reference Information	12
SAC	Loop SAC	13
SAC	Service, Promotion, Allowance, or Charge Information	14
DTM	Date/Time Reference	16
TD5	Carrier Details (Routing Sequence/Transit Time)	17
N1	Loop N1	19
N1	Party Identification	20
N3	Party Location	21
N4	Geographic Location	22
REF	Reference Information	23
PER	Administrative Communications Contact	24
PO1	Loop PO1	25
PO1	Baseline Item Data	26
PID	Loop PID	30
PID	Product/Item Description	31
PO4	Item Physical Details	32
CTT	Loop CTT	33
CTT	Transaction Totals	34
AMT	Monetary Amount Information	35
SE	Transaction Set Trailer	36
GE	Functional Group Trailer	37
IEA	Interchange Control Trailer	38